

# RUBIA XT



## MULTIGRADE OIL FOR DIESEL ENGINES

### APPLICATIONS

- For all turbocharged or normally aspired Diesel engines of vehicles operating in the most severe conditions whatever the seasons.
- Adapted for extended drain intervals (up to 30,000 km according to manufacturers).

### PROPERTIES

- Multigrade
- Very high viscosity index
- Excellent viscosity stability in operation
- Excellent detergency level
- High dispersancy level
- Excellent anti-wear and anticorrosion properties
- Very good antioxidant, antirust, antifoaming properties.

### CHARACTERISTICS

RUBIA XT	Units	SAE Grade	
		15W40	20W50
Volumetric mass at 15 °C	kg/m <sup>3</sup>	890	887
Viscosity @ 40 °C	mm <sup>2</sup> /s (cSt)	105	169
Viscosity @ 100 °C	mm <sup>2</sup> /s (cSt)	14.2	18.8
Viscosity Index	-	135	125
TBN	mg KOH/g	11	11
Flash point Cleveland	°C	225	212
Pour point	°C	-30	-30

The typical characteristics mentioned represent mean values

### SPECIFICATIONS

API CF 4/SJ  
ACEA E2  
MIL -L-2104 E  
MERCEDES BENZ 228.1

MAN 271  
VOLVO VDS  
CATERPILLAR TO-2

TOTAL LUBRICANTS  
P.O. Box : 52288  
Dubai, United Arab Emirates  
1/1

RUBIA XT  
N° TDS/DXB/09/12/336



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.